



PRODUCT INFORMATION

Lubrita Rust Pro OB 30 **Neat Corrosion Preventive Oil**

PRODUCT DESCRIPTION

Lubrita Rust Pro OB 30 is a mineral oil based corrosion preventive compound suitable for the wide range of application. These grades serve as lubricant as well as temporary protectives. It is formulated with anti-rust and anti corrosive additives. For best result metal surface should be clean and dry before **Lubrita Rust Pro OB 30** is applied. The protective film of these grades has lubricating properties and hence is not necessary to remove. However, if desired, the film can be removed by wiping.

PERFORMANCE BENEFITS

- Easy application by dipping, spraying, brushing, but the application surface must be cleaned and dried.
- Excellent Film Formation.
- Non-Staining
- Easy removal by wiping.
- Uniform coating on wide range coverage area.
- High degree of corrosion protection.
- Free of barium and other heavy metals.

APPLICATION

Lubrita Rust Pro OB 30 is for use as short terms inter- operational protective or for the treatment of components before wrapping or as a temporary protection of ferrous bar, rod and strip. The product is also suitable as flushing oil for the internal protection of engines and machinery.

PERFORMANCE LEVEL

TYPICAL CHARACTERISTICS

<i>S: no</i>	<i>Test Parameter</i>	<i>Typical Value</i>
1.	Appearance	Bright, Amber, Clear Fluids.
2.	Specific Gravity @ 29.5°C	.874
3.	Flash Point, COC, °C, Min	180
4.	Kinematic Viscosity cSt @ 40°C	32
5.	Coverage (sq. mt. /ltr)	60 – 80
6.	Film Thickness, Micron*	4 – 6



7.	Protection Months** – Indoors	2 – 3
	– Outdoors	Not recommended

* Figures are indicative only. Values depend on method of application and shape of components.

** Figures are indicative only. Protection depends on atmospheric conditions under storage.