



PRODUCT INFORMATION

LUBRITA UNIFLEET TURBO 15W40 / CF 4 **Premium High Performance Diesel Oil**

DESCRIPTION

LUBRITA UNIFLEET TURBO 15W40 / CF 4 is high-quality engine oil. It contains a set of enriching additives acting as antioxidants, corrosion inhibitors and improving cleaning and dispersion properties as well as lubrication, viscosity and temperature properties. This oil can be used in high-pressure engines of passenger and commercial vehicles, trucks and buses.

SPECIFICATIONS

Meets and Exceeds API CF-4 , MIL – L – 2104C, Cummins CES 20075

FEATURES & BENEFITS

1. Guarantees superior engine cleanliness and protection against corrosion.
2. Reduces engine wear by retarding deposits and carbon deposits formation.
3. Ensures easy start-ups at low temperatures.
4. Reduces the performance failure that might be caused by the sulphate ash content in the oil.
5. Helps in reducing refills.

RECOMMENDATIONS

Recommended specially for Turbo charged heavy/ light commercial vehicles, Tractors, Jeeps and Cars.

PERFORMANCE LEVEL

TYPICAL CHARACTERISTICS	
Specific Density at 29.5 °C	0.880
Kinematics Viscosity at 100° C	14.5-15.5
Viscosity Index (Min)	120
Flash Point, ° C	220 (T)
Pour Point ° C (Max)	-28
TBN,mg KOH /gm	9.5 - 10.5 Min.

* These are typical figures and do not constitute a specification.