



## PRODUCT INFORMATION

### LUBRITA UNISLIDE 32 / 68 / 220

#### Description:

**Lubrita Unislide 32 / 68 / 220** are stable, high quality oils specially compounded to provide efficient lubrication of machine slide-ways. These are adhesive, tacky and resist stick-slip, thereby assuring smooth, efficient operation. These products have excellent extreme pressure and film strength properties and meet the exact demand of slide way lubrication in grinders, planners, milling machines and other equipment having slow moving parts.

#### Features:

1. Excellent extreme pressure and film strength properties and meet the exact demand of slide lubricant.
2. Provide efficient lubrication of machine slide way stick slip, assuring smoothness & efficiency.

#### Typical Results:

Characteristics	Unislide 32	Unislide 68	Unislide 220
Color	Bright & Clear	Bright & Clear	Bright & Clear
Viscosity at 40°C,cst	28 – 34	66 – 70	210 – 230
Flash Point	> 190°C	> 195°C	> 198°C
Pour Point ,°C , Max	-3	-3	-3
Viscosity Index, Min	95	95	95

## HANDLING, HEALTH AND SAFETY

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing and keep away from combustible materials. Store under cover and away from any risk of pollution. Disposes off the used oil correctly, don't pour down drains, into watercourses or the soil.