



LUBRITA HYDROFLOW AW

DESCRIPTION

LUBRITA HYDROFLOW AW Hydraulic Oils are high quality anti wear type hydraulic oil designed to provide efficient and cost effective lubrication of hydraulic system and machinery. These products are formulated from high VI oils possessing excellent oxidation stability, anti wear, anti corrosion and lubricity properties.

LUBRITA HYDROFLOW Hydraulic oils are recommended for all types of industrial as well as mobile equipments like fork lift trucks, dumpers, blow molding and injection molding machines and various hydraulic equipments operating in industries.

FEATURES & BENEFITS

- ◆ High viscosity index due to highly refined base oils
- ◆ High resistance to oxidation resulting in longer service life
- ◆ Excellent anti-corrosion and anti-rust properties
- ◆ High resistance to foaming and good water oil separation ensures smooth and efficient operation.

PERFORMANCE LEVELS

- ◆ DIN 51524, Part 2
- ◆ Denison HF-2
- ◆ Vickers I-286-S
- ◆ IS 10522: 1983

TYPICAL CHARACTERISTICS

ISO Grade	32	46	68	100	150	220	320	460
Kinematic Viscosity, cSt @ 40°C	32	46	68	100	150	220	320	460
Kinematic Viscosity, cSt @ 100°C	5.7	7.4	9.2	11.1	16.1	22.1	27.3	34.1
Viscosity Index (min)	105	105	108	101	101	101	100	100
Flash Pt. (COC), °C	200	210	220	225	230	230	230	260
Pour Point, °C (Max)	-6	-6	-6	-6	-6	-3	-3	-3