



Product Name: Lubrita Lubrigrease EP 2

Description & Application:

Lubrigrease EP 2 is a lithium thickened lubricating grease based on mineral oil. The grease contains anti-oxidants, corrosion inhibitors and EP/AW additives.

The product is a state-of-the-art multipurpose EP 2 grease which can be used in various applications within given temperature limits. The lubricating grease offers good mechanical stability, load carrying capacity and corrosion protection, which makes it suitable for loaded bearings as well as wet environments.

Lubrigrease EP 2 is a high quality multipurpose grease that can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings. At high temperatures, Lubrigrease EPX 52 is recommended instead.

Specification:

Properties	Lubrigrease EP2
NLGI Grade	2
Appearance/Structure	Smooth, Buttery & Amber Yellow
Soap Type	Lithium
Worked Penetration @25°C, after 60 Strokes, 0.1mm units, ASTM D217	275
Drop Point, °C, ASTM D2265	195
Viscosity of Base Oil @ 40°C, cSt, ASTM D445	220
Viscosity of Base Oil @ 100°C, cSt, ASTM D445, Min	18
Copper Strip Corrosion, ASTM D4048	1 B
Four-Ball Weld Load, kg, ASTM D2596, Min.	280
Four-Ball Wear Scar Diameter, ASTM D2256, mm	0.42
Water Washout, 79°C, ASTM D1264, % wt	<8

Available Pack Size: 18 kg, 50 kg & 180 kg.