



Lubrita Unifleet Multi,SAE20W40,API CF

Product name: Lubrita Unifleet Multi 20W40,API CF

Features:Lubrita Unifleet Multi,SAE 20W40,CF is made from highly refined GroupII base stock with well balnced additive formulation suiting to diesel engine working in On road and off road equipments.

It meets MIL-L-2104C, plus Mack T -8 specifications.

It is recommended for use in all types of tractors enegines which have been in prolonged used condition of makes like M&M, John Deer, Sonalika, TAFE, Eicher, Escorts, New Holland etc. Besides, it is also recommended for HCVs and LCVs.

Benefits:

- -Specially formulated product for diesel engines.
- -Resists soot related oil thickening in vehicles carrying heavy load.
- -Long engine life.
- -Reduce oil consumption.
- -Excellent engine protection.
- -Exceptional detergency properties ensures excellent cleaning of engine

Typical physical characteristics:

Property	Test method, ASTM	Unifleet Multi 20W40
Appearance	Visual	Clear Bright
Density @29.5 deg C,gm/ml	D 4052	0.8650
Kin. viscosity@40 deg C, cSt	D 445	120
Kin. Viscosity @100deg C,cSt	D 445	14.6
Viscosity index	D 2270	105
Total base no, mg KOH/gm	D 2896	8
Flash point(COC),deg C	D 92	210
Pour point,deg C	D 97	-10

Company name: LUBRITA INDIA Pvt Limited.
Corporate Indentity No.: U23203MH2013PTC249528

Regd Off: 116, 1st Floor, Plot No-2,3,4, Commodity Exchange, Building, Sector -19, Vashi, Navi Mumbai - 400705

Tel.: +91 22 42954438 Email. <u>info@Lubrita.co.in</u> Web. www.Lubrita.com