



LUBRITA UNITRANS 80W 90

PRODUCT: GEAR OIL 80 W 90

INTRODUCTION:

Lubrita Unitrans 80W90 is extreme pressure automotive gear lubricants. These oils are blended from specially selected base stocks and additives to provide extreme pressure, anti-rust, anti-corrosion characteristics.

APPLICATION: Lubrita Unitrans 80W90 GEAR oils is recommended for passenger car, bus and highway truck for the lubrication of hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.

PERFORMANCE LEVEL: Gear Oil meet the performance level of API service classification GL-4.

MB 235.0, MAN 342 Type M-1, DAF, Voith 3.325-339, Volvo 97310/97316,

BENEFITS

- Exceptional protection against foaming, rust and corrosion.
- Excellent compatibility with all seals to control the leakage.
- Outstanding resistance to gear distress under high-speed, shock-load, high-speed, low-torque and low-speed, high-torque conditions.
- Right level of detergency to ensure a clean system.

Typical Physical Characteristics

SAE Viscosity Grade	80W/90
Density @ 15°C, kg/cu.m	0.895
Kinematic Viscosity @ 40°C, cSt	164.1
Kinematic Viscosity @ 100° C, cSt	15.5
Viscosity Index	95
Flash Point, COC, °C	200
Pour Point, °C	-24