



LUBRITA UNITRANS GEAR OIL 85W 140 GL-5

INTRODUCTION: Lubrita Unitrans Gear oil SAE 85 W /140 are extreme pressure automotive gear lubricants. These oils are blended from specially selected base stocks and additives to provide extreme pressure, anti-rust, anti-corrosion characteristics

APPLICATION: It is recommended for passenger car, bus and highway truck for the lubrication of hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.

PERFORMANCE LEVEL: GEAR OIL meet the performance level of API service classification GL-5

IS: 1118-1992 EP Type GL-5. US Military MIL-L-2105D, MB 235.0, MAN 342 Type M-1, DAF, Voith 3.325-339, Volvo 97310/97316, Renault

BENEFITS:

- Excellent compatibility with all seals to control the leakage.
- Outstanding resistance to gear distress under high-speed, shock-load, high-speed, low-torque and low-speed, high-torque conditions.
- Right level of detergency to ensure a clean system.
- **Typical Physical Characteristics**

SAE Viscosity Grade	85W/140
Density @ 15°C, kg/cu.m	0.905
Kinematic Viscosity @ 40°C, cSt	400
Kinematic Viscosity @ 100° C, cSt	27
Viscosity Index	92
Flash Point, COC, °C	240
Pour Point, °C	-18