

MATERIAL SAFETY DATA SHEET

Product Identification and Emergency Information

Trade Name Identity: International Anti-Rust #118-H

Date: October 25, 2007

Manufacturers Name: International Chemical Company

Address: 2628 North Mascher Street
Philadelphia, PA 19133

Emergency Telephone Number: 215-739-2313

Chemtrec: 1-800-424-9300

Chemical Name: Not Applicable For This Mixture

Synonyms: None

Chemical Family: Rust Inhibitor, Solvent Vehicle

Appearance and Odor: Transparent Amber Liquid; Mild Solvent Odor

Hazardous Mixtures of Other Liquids, Solids or Gases

None

Physical Data

Boiling Point, F: 360, Minimum

Vapor Pressure, mm Hg: 3.0 Maximum at 100 F.

Vapor Density (Air =1): Approximately 5.2

Specific Gravity (Water = 1): 0.80

Evaporation Rate (Toluene = 1): Less Than 0.1

Solubility in Water: Negligible

Fire and Explosion Hazard Data

Flash Point: 150 Minimum, Cleveland Open Cup

Flammable Limits in Air: Lower: 1.0%; Upper: 7.0%

Extinguishing Media: Foam, Dry Chemical, Carbon Dioxide, Water Mist or Fog

Special Fire Fighting Procedures: Cool Drums with Water Spray. Avoid Breathing Vapors or Fumes. Use Self-Contained Breathing Apparatus in Enclosed Areas.

Unusual Fire and Explosion Hazards: Sealed Containers may Explode if Involved in Fire. Empty Containers Retain Product Residue and May Explode if Welded, Heated, Pressurized, or Exposed to Flame. Mists or Sprays may be Ignited by Spark or Flame at Temperatures below the Normal Flash Point.

Health Hazard Data

Threshold Limit Value: 100 ppm (Inhalation)

Effects of Overexposure: Product is Irritating to Eyes and Mucous Membranes, and May be Irritating to Skin and Digestive Tract, Depending upon Extent of Exposure. Vapors or Mists, if Inhaled, May be Irritating to Lungs and affect the Nervous System.

Acute Effects:

Eye Contact: Causes Severe Irritation

Skin Contact: Will Defat the Skin, Causing Drying and Possible Irritation. May Cause Dermatitis upon Prolonged or Repeated Contact.

Ingestion: Causes Irritation and Nausea.

Inhalation: Inhalation of High Vapor Concentrations Causes Irritation, Dizziness, Headaches, Nausea. Unconsciousness may result from Extreme Overexposure.

Chronic Effects: Same as Acute Effects

Hazardous Components

Chemical Name: Petroleum Distillate

Synonyms: aliphatic Hydrocarbon Solvent

Primary Routes of Entry: Skin, Inhalation

Type of Hazard: Combustible Liquid; Central nervous System Depressant; Irritant

OSHA Permissible Exposure Limit (Time Weighted Average, 8-hour Day): 100 ppm (Inhalation)

ACGIH TLV (Time Weighted Average, 8-Hour Day): 100 ppm (Inhalation)

Toxic Chemical Release Reporting

The Following Chemicals In This Product Are Subject To Reporting Under Section 313 Of Sara Title III;

<u>Chemical</u>	<u>CAS Number</u>	<u>Maximum Concentration Percent by Weight</u>
Barium Compounds	7440-39-3	6

I. A.R. #118-H (Continued)

Emergency and First Aid procedures

Eyes: Flush with Clear Water for at least 15 Minutes, with Eyelids Open. Call Physician if Irritation Persists.

Skin: Remove Contaminated Clothing. Wash Affected Area Thoroughly with Soap and Water.

Ingestion: If Patient is Conscious, Administer Water. Do Not Induce Vomiting. Do not give Anything by Mouth to an Unconscious Person. Call physician immediately.

Inhalation: If Overcome by Vapor Remove to Fresh Air. Call Physician Immediately. If Breathing has Stopped or is Irregular, Apply Artificial Respiration and Administer Oxygen.

Reactivity Data

Stability: Stable

Conditions To Avoid: Avoid Contact with Oxidizing Agents, Open Flames, Sparks, Very Hot Metal Surfaces.

Hazardous Decomposition Products Thermal Decomposition Produces Carbon Dioxide, Carbon Monoxide, Oxides of Sulfur and Smoke.

Polymerization Potential: Not Present

Spill or Leak Procedures

Steps To Be Taken If Material is Released or Spilled:

Ventilate Area and Eliminate All Open Sparks, Flames, and Other Sources of Ignition. Use Trained Personnel Equipped with Appropriate Eye, Respiratory and Skin Protection (See Special Protection information below). Contain Spillage and Transfer to Approved Salvage Containers. Avoid Splashing Or Misting. Keep Out of Watercourses. Residue may be Absorbed with Inert Material such as Sand, Clay, or Earth.

Waste Disposal Method:

Incinerate under Controlled Conditions or Dispose of at Approved Disposal Site or Facility. Assure Conformity with all Applicable Disposal Regulations.

Special Protection Information

Respiratory Protection: None Required under Most use Conditions. Use Only with Adequate Ventilation. Use NIOSH Approved Hydrocarbon Vapor Canister or Supplied-Air Equipment, if Needed, in Enclosed Spaces or Confined Areas, or in High Vapor Concentrations where the TLV is Exceeded. Refer to 29 CFR 1910.134 to Assure Compliance

Ventilation: Provide Adequate Ventilation to Avoid Vapor Concentrations Exceeding the TLV in Employee Work Areas.

Protective Gloves: None Required. Solvent Resistant Rubber or Plastic Recommended where Prolonged or Repeated Contact is Expected.

Eye Protection: Chemical Splash Goggles or Safety Glasses with Side Shields.

Other Protective Equipment: Solvent Resistant Rubber or Plastic Outer Garment and Boots where Saturation of Clothing and Footwear is Possible. Eye Wash Station. Equipment Must be in Accordance with 29 CFR 1910.132 and 29 CFR 1910.133.

Special Precautions

Precautions to be Taken in Handling and Storing:

Store Indoors in Dry, Cool Area away from Sparks, Open Flames and Excessive Heat. Keep Container Sealed. Replace Closure after each Withdrawal. Make sure Closure is Sealed before Moving Container. Avoid Prolonged or Repeated Contact with Skin and Wash Thoroughly after Handling. Avoid Breathing Vapors.

Other Precautions:

Do not Permit Employees to Handle Product without Training and Proper Protective Equipment. Read Material Safety Data Sheet Before using Product.

Wash with Soap and Water before Eating, Drinking, Smoking, or using Toilet Facilities.

Launder Contaminated Clothing before Reuse.

Remove contaminated shoes and dry before reuse

Disclaimer: The information-contained herein has been compiled from sources considered to be dependable and is accurate as of the date issued. However, since data, safety standards, and governmental regulations are subject to change and the conditions of handling and use are beyond the control of International Chemical Company and/or any of its representatives, International Chemical Company makes no warranty regarding the accuracy of such information or its suitability for any purchasers and/or users for any consequence of its use. The information and data contained in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material. Safe handling and use remains the responsibility of the purchaser and/or user and the purchaser and/or user has the sole responsibility to determine the suitability of the materials for any use and the manner of the use contemplated. International Chemical Company assumes no responsibility for injury to the recipient or to third persons for any damage to any property and the recipient assumes all such risks.