



INTERNATIONAL CHEMICAL CO.
2628-48 N. Mascher Street • Philadelphia, PA 19133
P: 215-739-2313 • F: 215-423-7171 • www.e-icc.com

RUST INHIBITORS AND PREVENTATIVES

FEATURES

- 3150 Hours of Protection at 100°F & 100% Humidity (ASTM D-1748)
- 88 Hours of Salt Spray Resistance
- Suppress Fingerprint Corrosion and Aluminum Oxidation
- Excellent Protection During Periods of Indoor Storage
- Effective Protection in Acid Fume and Salt Spray Environments
- Water-Displacing
- Low Viscosity
- Dry-To-The-Touch Residual Film

INTERNATIONAL ANTI-RUST #99

DESCRIPTION

International Anti-Rust #99 is a solvent-based, water-displacing rust preventative engineered to deposit a dry-to-the-touch film on metal surfaces.

International Anti-Rust #99 is engineered with a low viscosity to aid penetration and provide free drainage following applications.

OPERATIONAL DATA

| | |
|--|------------|
| All Operations | 100% |
| Humidity Cabinet Performance (ASTM D-1748, 95% RH/38 °C) | 3150 Hours |
| Salt Spray Resistance (ASTM B117) | 88 Hours |

Note: **International Anti-Rust #99** should be used as received and may be applied with dip, spray and/or brush equipment. When wet parts are dipped, several minutes of submergence should be allowed for complete displacement of water. The protection durations noted above are typical for most operations. Your International Chemical Company Representative will work closely with you to determine the ideal methods of use for your particular operations.

TYPICAL CHARACTERISTICS

| | |
|--------------------------|----------------------------|
| Appearance | Transparent Amber Liquid |
| Odor | Mild, Mineral Spirits Odor |
| Specific Gravity, 15.5°C | 0.82 |
| Flash Point, T.C.C. | 40°C, Minimum |

