



PRODUCT INFORMATION

LUBRITA DEO HDM 20W40 API CF-4

(Premium Multi-grade Engine Oil)

DESCRIPTION

LUBRITA DEO HDM 20W40 engine oil is formulated on the base of selectively treated solvent de-waxed and hydro refined oil distillates received from crude oil. It contains a properly selected package of anti-oxidation and anti-corrosion additives, improving the washing and dispersant qualities as well as lubrication, viscosity and high temperature attributes.

APPLICATION

LUBRITA DEO HDM 20W40 is mineral oil based multi-seasonal engine oil. It is designed specially for the protection of the most technologically advanced high-pressure engines like aspirated and particularly those with turbo-charged diesel and gasoline engines running even under the toughest conditions.

LUBRITA DEO HDM 20W40

excellent quality makes it versatile and optimum for use in personal carriers and commercial goods and passenger transport vehicles, earthmoving equipments and agricultural vehicles.

SPECIFICATIONS

Meets and Exceeds API CF4, IS: 13656-2002, Type E-DL4, US MIL-L-2104 C Performance level.

FEATURES & BENEFITS

1. Its detergency and dispensability allows for a clean engine by keeping crud and carbon in suspension and preventing build-up on oil lines, segments, and pistons.
2. Multi grade oil, facilitating cold start-up and use in wide range of weather conditions.
3. Safeguards against engine corrosion due to its specific formulation.
4. Excellent anti-wear properties, minimizing frictions.
5. Reduces lubricant consumption and refills.

PERFORMANCE LEVEL

TYPICAL CHARACTERISTICS	
Specific Density at 29.5 °C	0.8875
Kinematics Viscosity at 100°C	14-15.5
Viscosity Index (Min)	110
Flash Pt. (COC), °C	220 (T)
Pour Point (Max)	-25
TBN,mg KOH /gm	9.5 -10.00

* These are typical figures and do not constitute a specification.